

Material Safety Data Sheet

Page: 1 of 5

Infosafe No. LPUBA Issue Date : March 2005 ISSUED by BARNES

Product Name : **PROCAST® PART A**

Classified as hazardous according to criteria of NOHSC

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Product Name PROCASTM PART A
Product Use Casting resin.
Company Name Barnes Products Pty Ltd (ABN 004 011 456)
Address 6 Homedale Road Bankstown
NSW 2200
Emergency Tel. (02) 9793 7555
Telephone Number/Fax Tel: (02) 9793 7555 Fax: (02) 9793 7091

Other Names Name Product Code
SUPERCAST® PART A

Other Information Information provided has been prepared in good faith and believed to be correct. Barnes Products Pty Limited make no warranty either express or implied as to completeness, accuracy thereof, misuse or misinterpretation of this information.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Name	CAS	Proportion
	Distillates (petroleum), catalytic reformer fractionator residue, low boiling	68477-31-6	30-60 %
	Diphenylmethane-4,4'-diisocyanate	101-68-8	10-30 %
	Naphthalene	91-20-3	10-30 %

3. HAZARDS IDENTIFICATION

Classified as hazardous according to the criteria of NOHSC.
Classified as a dangerous good according to the ADG Code.

RISK PHRASES:

R20/22 Harmful by inhalation and if swallowed.
R36/37/38 Irritating to eyes, respiratory system and skin.
R42/43 May cause sensitisation by inhalation and skin contact
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES:

S23 Do not breathe gas/fumes/vapour/spray.
S24/25 Avoid contact with skin and eyes.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
S51 Use only in well ventilated areas.
S61 Avoid release to the environment. Refer to special instructions/safety data sheet.
S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

4. FIRST AID MEASURES

Inhalation Remove the source of contamination or move the victim to fresh air. Ensure airways are clear and have qualified person give oxygen through a face mask if breathing is difficult. If symptoms develop seek medical attention.

Ingestion Do NOT induce vomiting. Wash out mouth with water. Do not give anything by mouth to an unconscious person. Seek medical attention.

Skin Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash before reuse or discard. If symptoms develop seek medical attention.

Material Safety Data Sheet

Infosafe No. LPUBA Issue Date : March 2005 ISSUED by BARNES

Product Name : PROCAST® PART A

Classified as hazardous according to criteria of NOHSC

Eye If contact with the eye(s) occur, wash with running water holding eyelid(s) open. Take care not to rinse contaminated water into the non-affected eye. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. In all cases of eye contamination it is a sensible precaution to seek medical advice.

First Aid Facilities Eye wash and normal washroom facilities.

Advice to Doctor Treat symptomatically or consult a Poisons Information Centre (Phone 131 126).

5. FIRE FIGHTING MEASURES

Extinguishing Media Keep containers cool with water spray. Do not use water in a jet. Water spray, foam, carbon dioxide and dry powder.

Specific Hazards Combustible liquid. This product will burn if exposed to fire.

Hazardous Combustion Products Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide, carbon dioxide, oxides of nitrogen, aldehydes and traces of hydrogen cyanide.

Precautions in connection with Fire Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Wear appropriate personal protective equipment and clothing to minimise exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unnecessary personnel. If possible contain the spill. Place inert absorbent material onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labelled container. Do not dilute material but contain. Dispose of waste according to federal, Environmental Protection Authority and state regulations. If large quantities of this material enter the waterways contact the Environmental Protection Authority, or your local Waste Management Authority.

7. HANDLING AND STORAGE

Handling Use in a well ventilated area. DO NOT store or use in confined spaces. Build up of mists or vapours in the atmosphere must be prevented. Avoid breathing in spray or mists or vapours. Do not use near welding or other ignition sources and avoid sparks. Do not smoke. When dealing with large quantities, repeated or prolonged skin exposure without protection should be prevented in order to lessen the possibility of skin disorders. It is essential that all who come into contact with this material maintain high standards of personal hygiene ie. washing hands prior to eating, drinking, smoking or using toilet facilities.

Storage Store in a cool, dry well-ventilated area away from heat, sources of ignition, oxidising agents, foodstuffs, and clothing and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all State and Federal regulations.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Exposure Limits No exposure standards have been established for this material by the National Occupational Health & Safety Commission (NOHSC). However, exposure standards for ingredients are stated below.

SUBSTANCE	TWA		STEL		NOTICES
	ppm	mg/m ³	ppm	mg/m ³	
Diphenylmethane-4,4'-diisocyanate	-	0.02	-	0.07	Sens
Naphthalene	10	52	15	79	

'Sen' notice - sensitiser. The substance can cause a specific immune response in some people. An affected individual may subsequently react to exposure to minute levels of that substance.

Material Safety Data Sheet

Infosafe No.	LPUBA	Issue Date : March 2005	ISSUED by BARNES
--------------	-------	-------------------------	------------------

Product Name : **PROCAST® PART A**

Classified as hazardous according to criteria of NOHSC

Other Exposure Information	TWA - the Time-Weighted Average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life. STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday. According to current knowledge these concentrations should neither impair the health of, nor cause undue discomfort to, nearly all workers.
Respiratory Protection	If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependant upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices.
Eye Protection	Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection	Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
Body Protection	Wear appropriate clothing including chemical resistant apron where clothing is likely to be contaminated. It is advisable that a local supplier of personal protective clothing is consulted regarding the choice of material.
Eng. Controls	Use with good general ventilation. If mists or vapours are produced local exhaust ventilation should be used.
Other Information	No biological limit allocated.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Light to dark amber viscous liquid
Odour	Naphtha odour
Melting Point	Not available.
Boiling Point	>205°C (decomposes)
Solubility in Water	Insoluble, reacts with water
Specific Gravity (H2O=1)	1.2
pH Value	7.8
Vapour Pressure	< 0.0001 mmHg
Vapour Density (Air=1)	Approx. 6
Volatile Component	40%
Flash Point	95.5°C
Flammability	Classified as a Class C1 (COMBUSTIBLE LIQUID) for the purposes of storage and handling, in accordance with the requirements of AS1940. This product should be stored and used in a well ventilated area away from naked flames, sparks and other sources of ignition.
Ignition Temperature	Not available
Flammable Limits LEL	Not available
Flammable Limits UEL	Not available

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions of storage and handling.
Hazardous Polymerization	May occur at temperatures above 175°C and on contact with water resulting in the emission of carbon monoxide, carbon dioxide and ammonia.

Material Safety Data Sheet

Page: 4 of 5

Infosafe No. LPUBA Issue Date : March 2005 ISSUED by BARNES

Product Name : **PROCAST® PART A**

Classified as hazardous according to criteria of NOHSC

Materials to Avoid Incompatible with water, strong bases, alcohols, metal compounds and surface active agents. Will cause some corrosion to copper alloys and aluminium.

Hazardous Decomposition Products Thermal decomposition at temperatures greater than 205°C may result in the release of toxic and/or irritating fumes including carbon monoxide, carbon dioxide, oxides of nitrogen, aldehydes and traces of hydrogen cyanide.

Hazardous Reaction Will react with water, strong bases, alcohols, metal compounds and surface active agents.

Conditions to Avoid Avoid moisture, heat, direct sunlight, open flames or other sources of ignition. Avoid temperatures greater than 175°C.

11. TOXICOLOGICAL INFORMATION

Toxicology Information LC50 (rat, inhalation) = approx. 370 mg/cm/4H
LD50 (rat, oral) = > 10,000 mg/kg
LD50 (rabbit, skin) = > 10,000 mg/kg

Inhalation Harmful by inhalation. Inhalation of product vapours will cause irritation of the nose, throat and respiratory system. Breathing vapour may cause an asthma like reaction.

Ingestion Harmful if swallowed. Ingestion of this product will irritate the gastric tract causing nausea and vomiting.

Skin Irritating to skin resulting in redness and itching.

Eye Irritating to eyes. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Chronic Effects Prolonged or repeated skin contact may lead to allergic contact dermatitis and sensitisation in some individuals. Prolonged or repeated exposure through inhalation of vapours/fumes may lead to sensitisation and occupational asthma.

12. ECOLOGICAL INFORMATION

This product is very toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment.

Environ. Protection Prevent this material entering waterways, drains and sewers.

Mobility No data is available for this material.

Persistence / Degradability No data is available for this material.

Ecotoxicity Aquatic LC50 (24hr) > 500mg/L

13. DISPOSAL CONSIDERATIONS

Dispose of waste according to federal, EPA and state regulations. Labels should not be removed from containers until they have been cleaned. Do not cut, puncture or weld on or near containers. Empty containers may contain hazardous residues. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers. Advise combustible nature.

14. TRANSPORT INFORMATION

This material is a Class 9 - Miscellaneous Dangerous Good according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. These substances are incompatible in a placard load with any of the following:

- Class 1, Explosives (when the class 9 substance is a fire risk substance),
- Class 5.1, Oxidizing agents (when the class 9 substance is a fire risk substance), and
- Class 5.2, Organic peroxides (when the class 9 substance is a fire risk substance).

U.N. Number 3082

Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S.* - (CONTAINS NAPHTHALENE)

DG Class 9

Hazchem Code 2X

Packaging Method 5.9.9

Packing Group III

EPG Number 9C1

Material Safety Data Sheet

Page: 5 of 5

Infosafe No.	LPUBA	Issue Date : March 2005	ISSUED by BARNES
--------------	-------	-------------------------	------------------

Product Name : **PROCAST® PART A**

Classified as hazardous according to criteria of NOHSC

IERG Number 47

15. REGULATORY INFORMATION

Risk Phrase
R20/22 Harmful by inhalation and if swallowed.
R36/37/38 Irritating to eyes, respiratory system and skin.
R42/43 May cause sensitisation by inhalation and skin contact
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Phrase
S23 Do not breathe gas/fumes/vapour/spray
S24/25 Avoid contact with skin and eyes.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
S51 Use only in well ventilated areas.
S61 Avoid release to the environment. Refer to special instructions/safety data sheet.
S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Poisons Schedule S6

Hazard Category Harmful, Irritant, Dangerous for the environment

16. OTHER INFORMATION

Contact Person/Point

SDS History MSDS Creation: March 2005
...End Of MSDS...

Material Safety Data Sheet

Page: 1 of 4

Infosafe No. LPUBL Issue Date : March 2005 ISSUED by BARNES

Product Name : **PROCAST® PART B**

Not classified as hazardous according to criteria of NOHSC

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Product Name PROCAS[®] PART B
Product Use Casting resin.
Company Name Barnes Products Pty Ltd (ABN 004 011 456)
Address 6 Homedale Road Bankstown
NSW 2200
Emergency Tel. (02) 9793 7555
Telephone Number/Fax Tel: (02) 9793 7555 Fax: (02) 9793 7091

Other Names	<u>Name</u>	<u>Product Code</u>
	SUPERCAST [®] PART B	

Other Information Information provided has been prepared in good faith and believed to be correct. Barnes Products Pty Limited make no warranty either express or implied as to completeness, accuracy thereof, misuse or misinterpretation of this information.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Information on Composition This product contains a blend of poly(oxyalkylene) polyether, amine bearing poly(oxyalkylene) polyether and petroleum distillates.

Ingredients	<u>Name</u>	<u>CAS</u>	<u>Proportion</u>
	Distillates (petroleum), catalytic reformer fractionator residue, low boiling	68477-31-6	30-60 %
	Other ingredients determined not to be hazardous		Balance

3. HAZARDS IDENTIFICATION

Not classified as hazardous according to the criteria of NOHSC.
Not classified as a dangerous good according to the ADG Code.

Risk phrases:
None applicable.

Safety phrases:
None applicable.

4. FIRST AID MEASURES

Inhalation Remove the source of contamination or move the victim to fresh air. Ensure airways are clear and have qualified person give oxygen through a face mask if breathing is difficult. If symptoms develop seek medical attention.

Ingestion Do NOT induce vomiting. Wash out mouth with water. Seek medical attention.

Skin Remove contaminated clothing and wash skin thoroughly with soap and water. Ensure contaminated clothing is washed before re-use or discard. If irritation develops, seek medical attention.

Eye If contact with the eye(s) occurs, wash with copious amounts of water holding eyelid(s) open. Take care not to rinse contaminated water into the non-affected eye. If symptoms persist seek medical attention.

First Aid Facilities Eye wash and normal washroom facilities.

Advice to Doctor Treat symptomatically or consult a Poisons Information Centre (Phone 131 126).

5. FIRE FIGHTING MEASURES

Extinguishing Media Do not use water in a jet. Keep containers cool with water spray. Use foam, carbon dioxide or dry chemical to extinguish fire.

Specific Hazards Classified as a Class C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS1940. This product should be stored and used in a well-ventilated area away from naked flames, sparks and other sources of ignition.

Material Safety Data Sheet

Infosafe No.	LPUBL	Issue Date : March 2005	ISSUED by BARNES
--------------	-------	-------------------------	------------------

Product Name : **PROCAST® PART B**

Not classified as hazardous according to criteria of NOHSC

Hazardous Combustion Products	Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide, carbon dioxide and oxides of nitrogen and ammonia.
Precautions in connection with Fire	Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Wear appropriate personal protective equipment and clothing to minimise exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unnecessary personnel. If possible contain the spill. Place inert absorbent material onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labelled container. Do not dilute material but contain. Dispose of waste according to federal, Environmental Protection Authority and state regulations. If large quantities of this material enter the waterways contact the Environmental Protection Authority, or your local Waste Management Authority.

7. HANDLING AND STORAGE

Handling	Use in a well ventilated area. DO NOT store or use in confined spaces. Build up of mists or vapours in the atmosphere must be prevented. Avoid breathing in spray or mists or vapours. Do not use near welding or other ignition sources and avoid sparks. Do not smoke. When dealing with large quantities, repeated or prolonged skin exposure without protection should be prevented in order to lessen the possibility of skin disorders. It is essential that all who come into contact with this material maintain high standards of personal hygiene ie. washing hands prior to eating, drinking, smoking or using toilet facilities.
Storage	Store in a cool, dry well-ventilated area away from heat, sources of ignition, oxidising agents, foodstuffs, and clothing and out of direct sunlight. Store between 18 and 30°C. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Exposure Limits	No value assigned for this specific material by the Australian National Occupational Health and Safety Commission (NOHSC).
Respiratory Protection	If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependant upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices.
Eye Protection	Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection	Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
Body Protection	Wear appropriate clothing including chemical resistant apron where clothing is likely to be contaminated. It is advisable that a local supplier of personal protective clothing is consulted regarding the choice of material.

Material Safety Data Sheet

Infosafe No.	LPUBL	Issue Date : March 2005	ISSUED by BARNES
--------------	-------	-------------------------	------------------

Product Name : **PROCAST® PART B**

Not classified as hazardous according to criteria of NOHSC

Eng. Controls Provide sufficient ventilation to keep airborne levels below the exposure limit. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 2430.3.1:1997 : Classification of hazardous areas - Examples of area classification - General, for further information concerning ventilation requirements.

Other Information No biological limit allocated.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Viscous liquid (colour determined by product)
Odour Distillate odour
Melting Point Not available
Boiling Point Not available (decomposes)
Solubility in Water Slightly soluble
Specific Gravity (H₂O=1) 1.06
pH Value Not available
Vapour Pressure Not available
Vapour Density (Air=1) Not available
Volatile Component 40%
Flash Point 118°C (Tag Closed Cup)
Flammability Classified as a Class C1 (COMBUSTIBLE LIQUID) for the purposes of storage and handling, in accordance with the requirements of AS1940. This product should be stored and used in a well ventilated area away from naked flames, sparks and other sources of ignition.
Ignition Temperature Not available
Flammable Limits LEL Not available
Flammable Limits UEL Not available

10. STABILITY AND REACTIVITY

Stability Stable under normal conditions of storage and handling.
Hazardous Polymerization Will not occur.
Materials to Avoid Isocyanates, acids and oxidising agents.
Hazardous Decomposition Products Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide, carbon dioxide, oxides of nitrogen and ammonia.
Hazardous Reaction Conditions to Avoid May react with isocyanates, acids and oxidising agents.
Heat, direct sunlight, open flames or other sources of ignition. This product is hygroscopic. Avoid contact with moisture. Do not expose to high temperatures for any length of time.

11. TOXICOLOGICAL INFORMATION

Toxicology Information No toxicity data is available for this specific product.
Inhalation Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.
Ingestion Ingestion of this product may irritate the gastric tract causing nausea and vomiting.
Skin May cause redness, itching and irritation.
Eye May cause eye irritation, tearing, stinging, blurred vision, and redness.
Chronic Effects Unknown.

12. ECOLOGICAL INFORMATION

Material Safety Data Sheet

Page: 4 of 4

Infosafe No.	LPUBL	Issue Date : March 2005	ISSUED by BARNES
--------------	-------	-------------------------	------------------

Product Name : **PROCAST® PART B**

Not classified as hazardous according to criteria of NOHSC

Environ. Protection	Do not allow product to enter drains, waterways or sewers.
Mobility	No data is available for this material.
Persistence / Degradability	No data is available for this material.
Ecotoxicity	No data is available for this material.

13. DISPOSAL CONSIDERATIONS

Dispose of waste according to federal, EPA and state regulations. Labels should not be removed from containers until they have been cleaned. Do not cut, puncture or weld on or near containers. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers. Advise combustible nature.

14. TRANSPORT INFORMATION

	Not classified as a Dangerous Good, according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.
U.N. Number	None Allocated
Proper Shipping Name	None Allocated
DG Class	None Allocated
Hazchem Code	None Allocated
Packing Group	None Allocated

15. REGULATORY INFORMATION

Poisons Schedule	S5
-------------------------	----

16. OTHER INFORMATION

Contact Person/Point

SDS History	MSDS Creation: March 2005 ...End Of MSDS...
--------------------	--